

There is nothing more important than the air we breathe.

2000 SERIES



SECOND WIND'S 2000 SERIES UNITS ARE A MAINSTAY OF THE INDOOR AIR QUALITY INDUSTRY. COMBINING HIGH INTENSITY ULTRAVIOLET LIGHT WITH PHOTO-CATALYTIC OXIDATION (PCO) ODOR CONTROL, THESE MODELS HELP **PROVIDE CLEAN PURIFIED AIR.**

OPTION Second Wind is pleased to offer the SF-1076R-O3, a lamp that introduces singlet oxygen to indoor air. This option provides a characteristic smell when reducing odors in unison with the PCO module. It can be ordered for existing installations or new purchases as an add-on option.



SECOND WIND AIR PURIFIERS USE ULTRAVIOLET LIGHT AND A PHOTO-CATAI YTIC PROCESS ΤO REDUCE MOLD. BACTERIA AND DECREASE VOLATILE ORGANIC COMPOUNDS IN YOUR INDOOR ENVIRONMENT.

IT'S A FANCY WAY OF SAYING THAT OUR PURIFIERS RETURN AIR TO THE WAY IT SHOULD BE: CLEAN.

THE SECOND WIND PHOTO-CATALYTIC PROCESS



UV LIGHT SHINES ON PHOTO-CATALYST HYDROXYL RADI-[TITANIUM DIOXIDE TIO₂]

CALS ARE FORMED

BIOAEROSOLS, POLLUTANTS AND ODORS ARE INACTIVATED



There is nothing more important than the air we breathe.

2000 SERIES

CENTER FOR DISEASE CONTROL ANALYSIS

Contributing Factors to Respiratory Problems (Allergies, Asthma and General Poor Health)



34% BIOAEROSOLS
 Micro-organisms, mold, bacteria, virus.

31% VOCs
 Chemical gases, solvents, odor causing contaminants.

35% PARTICULATES

Dust, dirt, pollen, spores, smoke, building materials.

	SF-2018	SF-2000	SF-2000-230
SYSTEM CAPACITY (MAX SQ. FT.)	2.5t (1700 ft ²)	5t (4000 ft ²)	5t (4000 ft ²)
POWER REQUIREMENT	110V	110V	230V
AMPERAGE DRAW	0.7A	0.7A	0.3A
LINE CORD	120V	120V	240V
STARTING	PLUG-IN	PLUG-IN	PLUG-IN
NUMBER OF LAMPS	1	2	2
LAMP SIZE	18"	18"	18"
*DEVICE UV INTENSITY (µW/cm2) 6" FROM SOURCE		3302	3302
*DEVICE UV INTENSITY (µW/cm2) 12" FROM SOURCE	829	1659	1659
*DEVICE UV INTENSITY (µW/cm2) 1 METRE FROM SOURCE	128	256	256
ODOR CONTROL	•	•	•
PHOTO-CATALYTIC OXIDATION (PCO) MODULE	•	•	•
REPLACEMENT LAMP(S)	SF-1076R		
REPLACEMENT BALLAST	SF-1060E-R		
OPTIONAL SINGLET OXYGEN LAMP (YIELDS RESIDUAL 03)	SF-1076R-03		

*KEITZ FORMULA/TABLE USED TO CALCULATE UV INTENSITY AT 6" AND 12"



› FDA CLASS II MEDICAL DEVICE K980745

- , IMPROVED AIR QUALITY
- REDUCES MOLD, AIRBORNE ALLERGENS, BACTERIA, GERMS
- PCO MODULE DECREASES OFF-GASES AND ODORS FROM AIRSTREAM

CANADIAN SALES

Canadian General Filters, Ltd.

400 Midwest Rd

Toronto, ON M1P3A9

Phone: (888) 216 9184



- IMPROVED AIR SYSTEM EFFICIENCY
- > LOW COST OPERATION
 - , TWO YEAR LAMP CHANGE
 - **, LIFETIME PCO MODULE**



You wouldn't drink this glass of dirty water. Why breathe dirty air?



www.generalaireIAQ.ca